



Product Service

CERTIFICATE

No. Z1A 114659 0009 Rev. 00

Holder of Certificate: **Four Design ApS**

Lucernemarken 17-19
5260 Odense S
DENMARK

Certification Mark:



Product:

Visitor chairs
4-legged chairs for general use

Tested according to:

DIN EN 16139:2014
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713231970

Valid until: 2027-01-20

Date, 2022-01-24

(Jens Biesenack)

CERTIFICATE

No. Z1A 114659 0009 Rev. 00

Model(s): FourCast2 Four / FourCast2 Four Loop armrest,
FourSure 44 / FourSure 44 Loop armrest

Parameters:

FourCast2 Four / FourCast2 Four Loop armrest	
Height [mm]	850
Width [mm]	515
Depth [mm]	500
Height seat surface [mm]	455
Height of the armrests [mm]	686
Clear distance between the armrests [mm]	586
General description	<ul style="list-style-type: none"> - Bended solid steel tube Ø16x2 mm, connections welded, chromium plated or coated - Polyshell (5-10.5 mm, PP GF 15%) or plywood veneer - Optional upholstered seat or seat/backrest cover - Optional without or with armrests made of plastic
FourSure 44 / FourSure 44 Loop armrest	
Height [mm]	840
Width [mm]	515
Depth [mm]	530
Height seat surface [mm]	455
Height of the armrests [mm]	695
Clear distance between the armrests [mm]	590
General description	<ul style="list-style-type: none"> - Bended solid steel tube Ø16x2 mm, connections welded, chromium plated or coated - Polyshell (5-10.5 mm, PP GF 40%) or plywood veneer - Optional upholstered seat or seat/backrest cover - Optional without or with armrests made of plastic